



Pharmaceutical refrigerator UMKS 6572, CFC-free, Chromium-nickel steel with insulating glass door



Symbol picture without drawer system

Stand-alone quality refrigerator from chromium-nickel steel with recirculated air cooling and 650 litres volume for professional storage and survey of pharmaceuticals. Optimal usage of cooled space by rational, tight storage organisation. Complete pull out of drawers including "H+H System" divider logic.

Flexible drawer divider system allows fast storage/removal of packed products and a quick reorganisation of product arrangement and card index.

Reliable drawer system of easy-to-care aluminium supports fast and lasting cooling of products. Very exact and stable metal treatment with [smooth edges](#).

Technical Data

Article	UMKS6572
Capacity	650 litres / 23.0 cu.ft.
Dimensions	HxWxD: 1990 x 765 x 800 mm / 6.53 x 2.51 x 2.62 ft
Dimensions incl. packing	HxWxD: 2060 x 810 x 850 mm / 6.76 x 2.66 x 2.79 ft
Volume incl. packing	1.42 m ³ / 50.15 cu.ft.
Weight incl. packing	221 kg / 487.2 lb.
Cooling technique	Recirculated-air cooling provided by top-mounted evaporator with fan
Defrosting	Fully automatic defrosting through evaporation
Temperature control	Continuously adjustable between +2°C to +15°C
Temperature monitor	Operating panel with digital temperature display, control displays for alarm and power on
Cooling agent	R 134 a
Power supply	250 watt for 220/230 volt, 50 Hz
Energy consumption	2.7 kWh/24 h
Illumination	Integrated into top of door frame with separate switch
Door hinges	Door fixing at choice
Door lock	Cylinder lock with 2 keys
Inner casing material	Chromium-nickel steel
Outer casing material	Chromium-nickel steel
Number of drawers	10 drawers (variable drawer quantity available upon request)
Drawer dimensions	HxWxD: 65 x 545 x 550 mm / 2.56" x 21.46" x 21.65"
Drawer surface	3.00 m ² / 46.50 sq.in.
Equipment	<ul style="list-style-type: none"> - Anodized aluminium drawers with ball bearing slides and security roll-stop. - Robust aluminium drawer system with vertically flexible aluminium dividers and horizontally flexible dividers of transparent PVC.
Options	<ul style="list-style-type: none"> - Analog, circular temperature chart recorder - Digital temperature monitoring with computer interface - Potential free contact for connection to central surveillance system - Acoustic temperature monitoring - Security temperature interceptor allowing for at least +1° C cooling temperature
Brand	allectric - Liebherr, AUSTRIA